AN: PAT 2000-308612
TI: Monitoring apparatus for e.g. intranet, internet
PN: **JP2000089818-A**
PD: 31.03.2000
AB: NOVELTY - A web server (24) transmits the fixed screen data
    (21d) and a display program (22p) to a fixed data memory (21)
    by access. The software memory of a monitoring terminal (30)
    stores a web software (31) for giving a variable data demand
    periodically to a data transmitter which sends the variable
    data to a variable data memory by variable data demand.
    DETAILED DESCRIPTION - The variable data memory updates the
    stored variable data. The fixed data memory stores the display
    program for combining the variable data with the fixed screen
    data to be shown on a monitoring screen (32).; USE - For e.g.
    intranet, internet. ADVANTAGE - Eases maintenance of intranet.
    Improves display velocity of monitoring apparatus and reduces
    transmission load. DESCRIPTION OF DRAWING(S) - The figure shows
    the model diagram of the monitoring apparatus. Fixed data
    memory 21 Fixed screen data 21d Display program 22p Web server
    24 Monitoring terminal 30 Web software 31 Monitoring screen 32
PA: (TOKE) TOSHIBA KK;
FA: **JP2000089818**-A 31.03.2000;
CO: JP;
IC: G05B-023/02; G06F-013/00;
MC: T01-H; T06-A08;
DC: T01; T06;
FN: 2000308612.gif
PR: JP0256732 10.09.1998;
FP: 31.03.2000
UP: 03.07.2000

既設監視装置
データ伝送機能 — 1
— 2
プラントデータ

広域監視装置 — 20
21, 21d   22, 22p
データ伝送機能 — 23
画面データ
表示用プログラム
Webサーバ — 24
初回表示時にダウンロード
・画面データ
・表示用プログラム

30
プラントデータ
監視端末
汎用Web閲覧ソフトウェア — 31
— 32
表示用プログラム
画面データ
22p   21d

固定画面は初回表示時に描画
可変部のみ定周期で編集